

Central Arid Zone Research Institute

(Indian Council of Agricultural Research)

Jodhpur (Rajasthan) 342 003





F. No.	8 (6) Drainage & plinth Rodent/13-14/Adm-V	Dated: 05/07/2014
To,		
	M/s	
Sub:	Repair of drainage system and plint protection of Rodent House and Rodent Co	ntrol Building at

Dear Sir(s),

CAZRI, Jodhpur.

You are requested to kindly quote your lowest rates keeping in view the following conditions in respect of the articles indicated overleaf/as per statement enclosed (Schedule to tender).

- 1. No advance payment will be made. However, the payment is normally made within 30 days from the date of receipt of Bill for execution the work **in good condition as per order**.
- 2. The quantity proposed in the quotation may be increased or decreased at the discretion of the authority while placing the order.
- 3. Quotation not found according to specification will be rejected/not considered.
- 4. The firm should also supply a copy of the authorized dealership certificate of the item, if applicable
- 5. Quotation should remain valid for 3 months from the date of quotation.
- 6. No. Form 'C' & 'D' for sales tax will be issued. Payment will be made at full rate, if applicable. However, the firm is required to produce the valid sales tax Registration No. The firm should also indicate PAN/TIN as per Income Tax Rules.
- 7. The Rates **should be clearly indicated in figure as well as in words**. While quoting the rates, it may be clearly indicated whether the items are inclusive or exclusive of ST, CST etc. in terms of percentage or in absolute term.
- 8. Works will have to be completed within stipulated periodas per work order failing which suitable penalty as indicated in the work order will be imposed.
- 9. Director, CAZRI, Jodhpur reserves the right to accept or reject any or all the quotation without assigning any reason.
- 10. All bids must be accompanied by a bid security/EMD of Rs. 3000/- of the estimated value of the cost, in the form of a Demand Draft of a scheduled commercial bank in India, in favour of ICAR Unit-CAZRI, Jodhpur. Without EMD quotation will not be considered.
- 11. The firm awarded the contract may/will have to furnish a performance security in the form of Bank Guarantee as per the proforma to be supplied along with work order or FDR pledged to "ICAR Unit CAZRI, Jodhpur" from a scheduled Commercial Banks or it may be deducted from bills for an amount which may vary from 5% to 10% of the value of the contract at the discretion of Director, which should remain valid for six months.
- 12. The quotation may be sent in the name of Director, CAZRI,Jodhpur to the office by courier/Registered Post/Speed Post in sealed cover superscribed with "Drainage of Rodent Control, CAZRI, Jodhpur." Due date 26/07/2014.
- 13. **The quotation** must be reached to this Office on or before **26/07/2014up to 3.00 PM** failing which it will not be considered. The quotation should be dropped in the Tender Box placed in the Adm.V.

Yours faithfully,



Central Arid Zone Research Institute

(Indian Council of Agricultural Research)





निविदा प्रपत्र (इस फार्म को निविदा प्रपत्र के साथ जमा कराना आवश्यक है)

निदेशक, केन्द्रीय शुष्क क्षेत्र अनुसंधान संस्थान, जोधपुर निम्नलिखित कार्य के लिए सीमित मोहरबन्द निविदाये आमंत्रित करते है

1.		air of drainage system and plinth protection of Rodent see and Rodent Control Building at CAZRI, Jodhpur.
2.	निविदादाता फर्म का नाम/पूर्ण पता	:
3.	टेलिफोन / मोबाइल नम्बर	÷
4.	निविदादाता फर्म का	: PAN No.
		: TIN No.
5.	बैंक का विवरण	: बैंक का नाम
		ः पता
		: बैंक का IFSC कोड :
		: बैंक का खाता नम्बर :
6.	निविदा प्रपत्र की कीमत	: रू. शून्य
7.	धरोहर (बयाना) राशि	: फ. 3,000/- Demand Draft/Pay Order/Banker Cheque ICAR Unit CAZRI, Jodhpur के पक्ष में देय हो
8.	कार्य पूर्ण करने की अवधि	: एक माह
9.	निविदा जमा कराने की अंतिम तिथि	: 26-07-2014 at 3.00 PM
10.	निविदा कार्य की विस्तृत सूचना काज	री की बेवसाईट <u>http://www.cazri.res.in</u> पर देखी जा सकती है।
11.	निविदा प्रपत्र काजरी, जोधपर की वेब	साईट से भी डाउन लोड किये जा सकते है।

निविदादाता के मोहर सहित हस्ताक्षर

Name of work:- Repairs of drainage system and plinth protection of Rodent house and Rodent control building at CAZRI, Jodhpur.

S.no.	Description	Quantity	Rate	Amount
1	Dismantling C.I. or asbestos rain water pipe with	Quantity	Tutt	Timount
_	fittings and clamps including stacking the			
	material within 50 metres lead:			
	75 to 80 mm dia pipe.	6 metre	@	
	73 to 80 mm dia pipe.	omene	@	
	100 mm dia pipe	24 metre	@	
	100 mm dia pipe	24 metre		
2	Dismantling of road gullty chamber of various			
	sizes including C.I. grating with frame including	6 nos.	@	
	stacking of use full materials near the site and	o nos.	@	
	disposal of unserviceable materials into			
	municipal dumps within 50 metres lead			
	including refilling the excavated gap.			
3	Dismantling old plaster or skirting raking out	25 sqm	@	
3	joints and cleaning the surface for plaster	23 sqiii	@	
	including disposal of rubbish to the dumping			
	ground within 50 metres lead.			
4	Earth work in surface excavation not exceeding			
 •	30 mm in depth but exceeding 1.5 m in width as			
	well as 10 sqm on plan including dsposal of			
	excavated earth upto 50 m and lift upto 1.5 m,			
	disposed soil to be leveled and neatly dressed: All kinds of soil.	150 gam	@	
	All killds of soil.	150 sqm	@	
5	Providing and laying in position cement concrete			
	of specified grade excluding the cost of			
	centering and shuttering – All work up to plinth			
	level:			
	1:3:6 (1 Cement : 3 fine sand : 6 graded stone	6 cum	@	
	aggregate 40 mm nominal size)			
6	Cement concrete flooring 1:2:4 (1 cement : 2			
	coarse sand : 4 graded stone aggregate) finished			
	with a floating coat of neat cement including			
	cement slurry, but excluding the cost of nosing			
	of step etc. complete.			
	40 mm thick with 20 mm nominal size stone	40 sqm	@	
	aggregate.			
7	Constructing brick masonry road gully chamber			
	50x45x60 cm with bricks of class designation 75			
	in cement mortar 1:4 (1 Cement : 4 Coars sand)			
	including 500x450 mm pre-cast R.C.C.			
	horizontal grating with frame complete as per			
	standard design:			
	With F.P.S. bricks	4 nos.	@	

S.no.	-2- Description	Quantity	Rate	Amount
8	Description Dismantling of manhole including R.C.C. top slab,	Quantity	Nate	Amount
0	C.I. cover with frame including stacking of useful			
	materials near the site and disposal of			
	unserviceable material into municipal dumps			
	within 50 m lead:			
	Rectangular manhole 90x80 cm and 45 cm deep	3 nos.	@	
9	Making connection of drain or sewer line with			
	existing manhole including breaking into and			
	making good the walls, floors with cement			
	concrete 1:2:4 mix (1 cement : 2 coarse sand : 4			
	graded stone aggregate 20 mm nominal size)			
	cement plastered on both side with cement mortar			
	1:3 (1 cement : 3 coarse sand) finished with a			
	floating coat of neat cement and making necessary			
	channels for the drain etc. complete.			
	For pipes 100 to 230 mm diameter	3 nos.	@	
10	D. 11			
10	Providing and laying non-pressure NP2 class (light			
	duty) R.C.C. pipes with collars jointed with stiff			
	mixture of cement mortar in the proportion of 1:2			
	(1 cement : 2 fine sand) including testing of joints			
	etc. complete:	10		
	100 mm dia. R.C.C. pipe	10 metre	@	
	150 mm dia. R.C.C. pipe	40 metre	@	
11	Providing and fixing square-mouth S.W. gully trap			
	grad 'A' complete with C.I. gating brick masonry			
	chamber with water tight C.I. cover with frame of			
	300x300 mm size (inside) the weight of cover to			
	be not less than 4.50 kg and frame to be not less			
	than 2.70 kg as per standard besign:			
	100x100 mm size P type		1	
	With F.P.S. Bricks class designation 75	6 nos.	@	
12	Coursed rubble masonry (second sort) with hard	3 1135.	<u> </u>	
	stone in foundation & plinth with:			
	Cement mortar 1:6 (1 cement : 6 coarse sand)	1.5 cum	@	
13	Supplying and fixing C.I. cover 300x300 mm	6 nos.	@	
	without frame for gully trap (standard pattern) the	J 1105.		
	weight of cover to be not less than 4.5 kg.			
14	Providing and fixing in position pre-cast R.C.C.			
1-7	manhole cover and frame of required shape and			
	approved quality.			
	Circular shape 500 mm internal diameter	4 nos.	@	
	one and shape 500 mm memai diameter	7 1105.		
15	Providing lead caulked joints to sand cast			
	iron/centrifugally cast (spun) iron pipes and			
	fittings of diameter:			
	75 mm	6 metre	@	
-		•		

S.no.	Description	Quantity	Rate	Amount
16	Providing and fixing soil, waste and vent pipes:			
	100 mm dia			
	Sand cast iron S&S pipe as per IS: 1729.	24 metre	@	
	75 mm dia.			
	Sand cast iron S&S pipe as per IS: 1729	6 metre	@	
17	Providing and fixing heel rest sanitary bend			
	100 mm			
	Sand cast iron S&S as per IS: 1729	6 nos.	@	
	75 mm			
	Sand cast iron S&S as per IS: 1729	6 nos.	@	
18	Providing and fixing bend of required degree with access door, insertion rubber washer 3 mm thick, bolts and nuts complete. 100 mm			
	Sand cast iron S&S as per IS: 1729	6 nos.	@	
	75 mm dia			
	Sand cast iron S&S as per IS: 1729	6 nos.	@	
	<u> </u>	<u> </u>	Total Rs.	
In wor	rds Rupees			

Signature with seal of Tenderer